


NSE vs. Talc, EPDM, extrusion, sulfur

Author:



Formulation

Ingredients	Description	phr
Vistalon 7700	Ethylene propylene diene rubber (M(1+8 (125 °C): 115 MU)	100
Zinkoxyd activ	Zinc oxide active	5
Edenor C18 98-100 GW	Stearic acid	2
Fillers	<i>see next slide</i>	300
Process Oil P 460	Paraffinic mineral oil, plasticizer	70
Kezadol GR	Calcium oxide, desiccant	10
Rhenogran ZBEC-70	Zinc dibenzyl dithiocarbamate, 70%, accelerator	2
Rhenogran CBS-80	N-cyclohexylbenzothiazole-2-sulfenamide, 80 %, accelerator	0.5
Rhenogran TP-50	Zinc dithiophosphate, 50%, accelerator	2
Rhenogran MBTS-80	2-Mercaptobenzthiazole, 80%, accelerator	1.3
Rhenogran S-80	Sulfur, 80 %, crosslinking agent	0.75
Rhenogran CLD-80	Caprolactam disulfide, 80 %, crosslinking agent	1
Total:		<u>494.55</u>



Filler selection

		Functionalization
Neuburg Siliceous Earth		-
Talc	Sillitin Z 86	-
	Aktisil AM	Amino
	Aktisil PF 216	Tetrasulfane
	Talc	-
	Talc, functionalized	Amino



Compounding and vulcanization

Compounding

Open mill Ø 150 x 300 mm

Batch weight approx. 1000 g

Mill temperature 50 °C

Mixing time approx. 15 min.

Vulcanization


The curing was carried out in a press at 180 °C

Time 5 min. or $t_{90} + 10\%$



Test standards – overview

Testing	Standard
Tensile test	DIN 53 504, S2
Compression set	DIN ISO 815-1, Type B
Hardness	DIN ISO 7619-1
Tear resistance - Trousers specimen	DIN ISO 34-1, A
Resistance to liquid media	DIN ISO 1817





[→ back to results](#)

Properties of vulcanizate




Hardness [Shore A]






Tensile strength [MPa]






Elongation at break [%]






Modulus 100 % [MPa]







Tear resistance [N/mm]






Compression set, 24 h / xx °C [%]






[→ back to results](#)

Immersion in deionized water 168 h / 95 °C




Δ Hardness [Shore A]






Δ Tensile strength [%]






Δ Elongation at break [rel.%]







Δ Weight [%]





Δ Volume [%]





[→ back to results](#)

Garvey Extrusion




Formulation for extrusion:

→ Extrusion was carried out without coactivator and cross linker.


In addition, 2 phr of the processing aid Aflux 42 were added

Ingredients	Description	phr
Vistalon 7700	Ethylene propylene diene rubber ML 1+8 (125 °C): 115 MU	100
Zinkoxyd active	Zinc oxide active	5
Edenor C18 98-100 GW	Stearic acid	2
Fillers		300
Process Oil P 460	Paraffinic mineral oil, plasticizer	70
Kezadol GR	Calcium oxide, moisture binder	10
Aflux 42	Processing aids	2
Total:		<u>489</u>




Garvey Extrusion

Extruder	Schwabenthan Polyester 30 R	
Screw diameter	[mm]	30
Process length	[mm]	450
Temperature set point head / Zone 1 / Zone 2	[°C]	150 / 40 / 40
Feeding strips	cold, untreated	








Garvey-die:





Garvey extrusion - extrudates at 2.0 m/min haul-off speed





We supply materials for good ideas!

HOFFMANN MINERAL GmbH
Muenchener Straße 75
DE-86633 Neuburg (Donau)

Phone: +49 8431 53-0
Internet: www.hoffmann-mineral.com
E-mail: info@hoffmann-mineral.com

Our applications engineering advice and the information contained in this memorandum are based on experience and are made to the best of our knowledge and belief, they must be regarded however as non-binding advice without guarantee. Working and employment conditions over which we have no control exclude any damage claim arising from the use of our data and recommendations. Furthermore we cannot assume any responsibility for patent infringements, which might result from the use of our information.